Swagger Supported by **SMARTBEAR**

/docs/swagger.json **Explore**

N.E.S.T. `0.1.0` `OAS3`

/docs/swagger.json

Authorize 🔓

user-related User related calls of the API. ⌄

POST `/api/v1/login` Attempt login.

GET `/api/v1/users/` Get a list of users. 🔓

DELETE `/api/v1/users/{email}` Deletes a user. 🔓

GET `/api/v1/users/{email}` Get details about a user. 🔓

PATCH `/api/v1/users/{email}` Updates a user. 🔓

repository-related Repository related calls of the API. ⌄

GET `/api/v1/repositories/` Get a list of repositories. 🔓

POST `/api/v1/repositories/` Creates a repository. 🔓

DELETE `/api/v1/repositories/{rid}` Deletes a repository. 🔓

GET `/api/v1/repositories/{rid}` Get details about a repository. 🔓

PATCH `/api/v1/repositories/{rid}` Updates a repository. 🔓

🔓

PUT   `/api/v1/repositories/{rid}` Overwrites a repository.

GET   `/api/v1/repositories/{rid}/alerts/` Get a list of a repository alerts.

GET   `/api/v1/repositories/{rid}/authorizations/` Get a list of a repository authorizations.

POST   `/api/v1/repositories/{rid}/authorizations/` Creates an authorization.

PUT   `/api/v1/repositories/{rid}/authorizations/` Update an authorization.

DELETE   `/api/v1/repositories/{rid}/authorizations/{email}` Delete an authorization.

GET   `/api/v1/repositories/{rid}/conditions/` Get a list of a repository conditions.

POST   `/api/v1/repositories/{rid}/conditions/` Creates a condition and attaches it to the repository.

GET   `/api/v1/repositories/{rid}/tweets/` Get a list of a repository tweets.

condition-related Condition related calls of the API. ⌄

DELETE   `/api/v1/conditions/{cid}` Delete a condition.

GET   `/api/v1/conditions/{cid}` Get the details of a condition.

PATCH   `/api/v1/conditions/{cid}` Update a condition.

alert-related Alert related calls of the API. ⌄

DELETE   `/api/v1/alert/{aid}` Deletes an alert.

GET   `/api/v1/alert/{aid}` Get details about an alert.

PATCH   `/api/v1/alert/{aid}` Updates an alert.

PUT   `/api/v1/alert/{aid}` Overrides an alert and the conditions.

POST   `/api/v1/repositories/{rid}/alerts/` Creates an alert and attaches it to the repository.

admin-only Admin only calls of the API. ⌄

POST `/api/v1/users/` Creates a user. 🔓

DELETE `/api/v1/users/{email}` Deletes a user. 🔓

debug Debug only calls of the API. ⌄

Schemas ⌄

Alert ›

AlertParameter ›

Authorization ›

Condition ›

ConditionParameter ›

CreateAlert ›

CreateAuthorization ›

CreateCondition ›

CreateRepository ›

CreateUser >

EmailParameter >

Error >

I_Login >

IntegerParameter >

Login >

Notification >

Repository >

RepositoryUpdate >

Success >

Tweet >

User >